

Устройства аварийного отключения

Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +(727)345-47-04

Беларусь +(375)257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: ddo@nt-rt.ru || сайт: <https://dold.nt-rt.ru/>



Emergency stop module LG 5925

- Width: 22,5 mm
- Cat. / PL acc. to EN ISO 13849-1: 4/e
- SIL CL acc. to IEC/EN 62061: 3
- Nominal voltage: AC, AC/DC
- Thermal current Ith max.: 8 A
- 1- / 2-channel: 1, 2



Emergency stop module, extremely small RK 5942

- Width: 17,5 mm
- Cat. / PL acc. to EN ISO 13849-1: 4/e
- SIL CL acc. to IEC/EN 62061: 3
- Nominal voltage: DC
- Thermal current Ith max.: 5 A
- 1- / 2-channel: 1, 2



Emergency stop module UF 6925

- Width: 17,5 mm
- Cat. / PL acc. to EN ISO 13849-1: 4/e
- SIL CL acc. to IEC/EN 62061: 3
- Nominal voltage: DC
- Thermal current Ith max.: 8 A
- 1- / 2-channel: 2



Emergency stop module with voltage failure detection BH 5903

- Width: 45 mm
- Cat. / PL acc. to EN ISO 13849-1: 4/e
- SIL CL acc. to IEC/EN 62061: 3
- Nominal voltage: DC
- Thermal current Ith max.: 5 A
- 1- / 2-channel: 1, 2



Safety module for elevator controls LG 5925/034

- Width: 22,5 mm
- Cat. / PL acc. to EN ISO 13849-1: 4/e
- SIL CL acc. to IEC/EN 62061: 3
- Nominal voltage: AC/DC
- Thermal current Ith max.: 5 A
- 1- / 2-channel: 1, 2



Emergency stop module BG 5925

- Width: 22,5 mm
- Cat. / PL acc. to EN ISO 13849-1: 4/e
- SIL CL acc. to IEC/EN 62061: 3
- Nominal voltage: DC, AC/DC
- Thermal current Ith max.: 5 A
- 1- / 2-channel: 1, 2



Emergency stop module BD 5987

- Width: 45 mm
- Cat. / PL acc. to EN ISO 13849-1: 4/e
- SIL CL acc. to IEC/EN 62061: 3
- Nominal voltage: AC, DC
- Thermal current Ith max.: 10 A
- 1- / 2-channel: 1, 2



Emergency stop module BD 5935

- Width: 45 mm
- Cat. / PL acc. to EN ISO 13849-1: 4/e
- SIL CL acc. to IEC/EN 62061: 3
- Nominal voltage: AC, DC
- Thermal current Ith max.: 10 A
- 1- / 2-channel: 1, 2



Emergency stop module BG 5924

- Width: 22,5 mm
- Cat. / PL acc. to EN ISO 13849-1: 4/e
- SIL CL acc. to IEC/EN 62061: 3
- Nominal voltage: AC, DC, AC/DC
- Thermal current Ith max.: 5 A
- 1- / 2-channel: 1, 2



Emergency stop module with time delay BH 5928

- Width: 45 mm
- Cat. / PL acc. to EN ISO 13849-1: 4/e
- SIL CL acc. to IEC/EN 62061: 3
- Nominal voltage: DC, AC/DC
- Thermal current Ith max.: 5 A
- 1- / 2-channel: 1, 2



Emergency stop module with voltage failure detection BL 5903

- Width: 90 mm
- Cat. / PL acc. to EN ISO 13849-1: 4/e
- SIL CL acc. to IEC/EN 62061: 3
- Nominal voltage: AC
- Thermal current Ith max.: 5 A
- 1- / 2-channel: 1, 2



Emergency stop module BN 5983

- Width: 100 mm
- Cat. / PL acc. to EN ISO 13849-1: 4/e
- SIL CL acc. to IEC/EN 62061: 3
- Nominal voltage: AC, DC
- Thermal current Ith max.: 10 A
- 1- / 2-channel: 1, 2



Emergency stop module IP 5924

- Width: 70 mm
- Cat. / PL acc. to EN ISO 13849-1: 4/e
- SIL CL acc. to IEC/EN 62061: 3
- Nominal voltage: AC, AC/DC
- Thermal current I_{th} max.: 5 A
- 1- / 2-channel: 1, 2



Emergency stop module LG 5924

- Width: 22,5 mm
- Cat. / PL acc. to EN ISO 13849-1: 4/e
- SIL CL acc. to IEC/EN 62061: 3
- Nominal voltage: AC, DC
- Thermal current I_{th} max.: 5 A
- 1- / 2-channel: 1, 2



Emergency stop module with time delay LG 5928

- Width: 22,5 mm
- Cat. / PL acc. to EN ISO 13849-1: 4/e
- SIL CL acc. to IEC/EN 62061: 3
- Nominal voltage: DC
- Thermal current I_{th} max.: 8 A
- 1- / 2-channel: 1, 2



Emergency stop module BN 5930.48/203

- Width: 100 mm
- Cat. / PL acc. to EN ISO 13849-1: 4/e
- SIL CL acc. to IEC/EN 62061: 3
- Nominal voltage: AC, DC
- Thermal current I_{th} max.: 10 A
- 1- / 2-channel: 1, 2



Emergency stop module BN 5930.48/204

- Width: 100 mm
- Cat. / PL acc. to EN ISO 13849-1: 4/e
- SIL CL acc. to IEC/EN 62061: 3
- Nominal voltage: AC, DC
- Thermal current I_{th} max.: 10 A
- 1- / 2-channel: 1, 2



Emergency stop module BO 5988

- Width: 100 mm
- Cat. / PL acc. to EN ISO 13849-1: 4/e
- SIL CL acc. to IEC/EN 62061: 3
- Nominal voltage: AC, DC
- Thermal current I_{th} max.: 10 A
- 1- / 2-channel: 1, 2



Safety module for safety switches LG 5925/920

- Width: 22,5 mm
- Cat. / PL acc. to EN ISO 13849-1: 4/e
- SIL CL acc. to IEC/EN 62061: 3
- Nominal voltage: DC
- Thermal current I_{th} max.: 8 A
- 1- / 2-channel: 1, 2



Emergency stop module BN 5930.48

- Width: 100 mm
- Cat. / PL acc. to EN ISO 13849-1: 4/e
- SIL CL acc. to IEC/EN 62061: 3
- Nominal voltage: AC, DC
- Thermal current I_{th} max.: 5 A
- 1- / 2-channel: 1, 2



Safety module, light curtain UG 6980/800

- Width: 22,5 mm
- Cat. / PL acc. to EN ISO 13849-1: 4/e
- SIL CL acc. to IEC/EN 62061: 3
- Nominal voltage: DC
- Thermal current Ith max.: 8 A
- 1- / 2-channel: 2



Light curtain controller with selectable operating modes BH 5902

- Width: 45 mm
- Cat. / PL acc. to EN ISO 13849-1: 4/e
- SIL CL acc. to IEC/EN 62061: 3
- Nominal voltage: DC
- Thermal current Ith max.: 5 A
- 1- / 2-channel: 1, 2



Light curtain controller LG 5925/900

- Width: 22,5 mm
- Cat. / PL acc. to EN ISO 13849-1: 4/e
- SIL CL acc. to IEC/EN 62061: 3
- Nominal voltage: DC
- Thermal current Ith max.: 8 A
- 1- / 2-channel: 1, 2



Safety mat switch gear BG 5925/910

- Width: 22,5 mm
- Cat. / PL acc. to EN ISO 13849-1: 4/e
- SIL CL acc. to IEC/EN 62061: 3
- Nominal voltage: DC
- Thermal current Ith max.: 5 A
- 1- / 2-channel: 2



Safety edge module LG 5944

- Width: 22,5 mm
- Cat. / PL acc. to EN ISO 13849-1: 4/e
- SIL CL acc. to IEC/EN 62061: 3
- Nominal voltage: AC/DC
- Thermal current Ith max.: 5 A
- 1- / 2-channel: 2



Two-hand safety relay LG 5933

- Width: 22,5 mm
- Cat. / PL acc. to EN ISO 13849-1: 4/e
- SIL CL acc. to IEC/EN 62061: 3
- Safety integrity level according to EN 574:
- III C Nominal voltage: AC, DC
- Thermal current Ith max.: 5 A



Two-hand safety relay BG 5933

- Width: 22,5 mm
- Cat. / PL acc. to EN ISO 13849-1: 4/e
- SIL CL acc. to IEC/EN 62061: 3
- Safety integrity level according to EN 574:
- III C Nominal voltage: AC, DC
- Thermal current Ith max.: 5 A



Two-hand safety relay BH 5933

- Width: 45 mm
- Cat. / PL acc. to EN ISO 13849-1: 4/e
- SIL CL acc. to IEC/EN 62061: 3
- Safety integrity level according to EN 574:
- III C Nominal voltage: AC, DC
- Thermal current Ith max.: 5 A



Two-hand safety relay BD 5980N

- Width: 45 mm
- Cat. / PL acc. to EN ISO 13849-1: 1/c
- SIL CL acc. to IEC/EN 62061: 1
- Safety integrity level according to EN 574:
- III A Nominal voltage: AC, DC
- Thermal current Ith max.: 5 A

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +(727)345-47-04

Беларусь +(375)257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: ddo@nt-rt.ru || сайт: <https://dold.nt-rt.ru/>