

Многофункциональные модули безопасности

Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +(727)345-47-04

Беларусь +(375)257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: ddo@nt-rt.ru || сайт: <https://dold.nt-rt.ru/>



Multifunction safety module BH 5910

- Width: 45 mm
- Cat. / PL acc. to EN ISO 13849-1: 4/e
- SIL CL acc. to IEC/EN 62061: 3
- Nominal voltage: DC
- Thermal current Ith max.: 5 A
- 1- / 2-channel: 1, 2
- Application: Emergency stop, Light barrier, Safety gate, Two-hand
- Safe output contacts, redundant NO contacts: 3



Multifunctional safety timer with instantaneous contacts UG 6960

- Width: 22,5 mm
- Cat. / PL acc. to EN ISO 13849-1: 4/e
- SIL CL acc. to IEC/EN 62061: 3
- Nominal voltage: DC
- Thermal current Ith max.: 8 A
- 1- / 2-channel: 2
- Application: Emergency stop, Light barrier, Safety mat, Safety gate, Two-hand
- Safe output contacts, redundant NO contacts: 4



Multifunctional safety timer UG 6961

- Width: 22,5 mm
- Cat. / PL acc. to EN ISO 13849-1: 4/e
- SIL CL acc. to IEC/EN 62061: 3
- Nominal voltage: DC
- Thermal current Ith max.: 8 A
- 1- / 2-channel: 2
- Application: Emergency stop, Light barrier, Safety mat, Safety gate, Two-hand
- Safe output contacts, redundant NO contacts: 2



Multifunctional safety module UG 6970

- Width: 22,5 mm
- Cat. / PL acc. to EN ISO 13849-1: 4/e
- SIL CL acc. to IEC/EN 62061: 3
- Nominal voltage: DC
- Thermal current Ith max.: 8 A
- 1- / 2-channel: 2
- Application: Emergency stop, Light barrier, Safety mat, Safety gate, Two-hand
- Safe output contacts, redundant NO contacts: 4



Multifunctional safety module UG 6980

- Width: 22,5 mm
- Cat. / PL acc. to EN ISO 13849-1: 4/e
- SIL CL acc. to IEC/EN 62061: 3
- Nominal voltage: DC
- Thermal current Ith max.: 8 A
- 1- / 2-channel: 2
- Application: Emergency stop, Light barrier, Safety mat, Safety gate, Two-hand
- Safe output contacts, redundant NO contacts: 2



Input module BH 5915.08/_1___

- Width: 45 mm
- Cat. / PL acc. to EN ISO 13849-1: 4/e
- SIL CL acc. to IEC/EN 62061: 3
- Application: Emergency stop, Light barrier, Safety gate
- Galvanically isolated inputs: Yes



Input module BH 5914.08/_0___

- Width: 45 mm
- Cat. / PL acc. to EN ISO 13849-1: 2/d
- SIL CL acc. to IEC/EN 62061: 2
- Application: Emergency stop, Light barrier
- Galvanically isolated inputs: Yes



Diagnostic module for Profibus DP BH 5552

- Width: 45 mm



Output module with output contacts BG 5912

- Width: 22,5 mm
- Cat. / PL acc. to EN ISO 13849-1: 4/e
- SIL CL acc. to IEC/EN 62061: 3
- Safe output contacts, redundant NO contacts: 3, 4
- Safe output contacts, time delay: 2, 3



Input module BG 5913.08/_0___

- Width: 22,5 mm
- Cat. / PL acc. to EN ISO 13849-1: 4/e
- SIL CL acc. to IEC/EN 62061: 3
- Application: Emergency stop, Light barrier, Safety gate, Two-hand
- Safety integrity level according to EN 574: III A, III C



Input module BG 5913.08/_1___

- Width: 22,5 mm
- Cat. / PL acc. to EN ISO 13849-1: 4/e
- SIL CL acc. to IEC/EN 62061: 3
- Application: Emergency stop, Light barrier, Safety gate, Two-hand
- Safety integrity level according to EN 574: III C



Input module BG 5913.08/_2___

- Width: 22,5 mm
- Cat. / PL acc. to EN ISO 13849-1: 4/e
- SIL CL acc. to IEC/EN 62061: 3
- Application: Emergency stop, Light barrier, Safety gate, Two-hand
- Safety integrity level according to EN 574: III C



Input module BG 5913.08/_3___

- Width: 22,5 mm
- Cat. / PL acc. to EN ISO 13849-1: 4/e
- SIL CL acc. to IEC/EN 62061: 3
- Application: Emergency stop, Light barrier, Two-hand
- Safety integrity level according to EN 574: III C



Input module BG 5914.08/_0___

- Width: 22,5 mm
- Cat. / PL acc. to EN ISO 13849-1: 2/d
- SIL CL acc. to IEC/EN 62061: 2
- Application: Emergency stop, Light barrier



Input module BG 5915.08/_1___

- Width: 22,5 mm
- Cat. / PL acc. to EN ISO 13849-1: 4/e
- SIL CL acc. to IEC/EN 62061: 3
- Application: Emergency stop, Light barrier, Safety gate



Control unit BH 5911

- Width: 45 mm
- Cat. / PL acc. to EN ISO 13849-1: 4/e
- SIL CL acc. to IEC/EN 62061: 3
- Application: Emergency stop, Light barrier
- Safe output contacts, redundant NO contacts: 2, 3



Input module BH 5913.08/_0___

- Width: 45 mm
- Cat. / PL acc. to EN ISO 13849-1: 4/e
- SIL CL acc. to IEC/EN 62061: 3
- Application: Emergency stop, Light barrier, Safety gate, Two-hand
- Safety integrity level according to EN 574: III A, III C
- Galvanically isolated inputs: Yes



Output module OSSD UG 6912.04/100

- Width: 22,5 mm
- Cat. / PL acc. to EN ISO 13849-1: 4/e
- SIL CL acc. to IEC/EN 62061: 3
- High current safety outputs: 4



Output module signal UG 6915/008

- Width: 22,5 mm
- Cat. / PL acc. to EN ISO 13849-1: 4/e
- SIL CL acc. to IEC/EN 62061: 3
- Signal outputs: 8



Output module signal UG 6915/016

- Width: 22,5 mm
- Cat. / PL acc. to EN ISO 13849-1: 4/e
- SIL CL acc. to IEC/EN 62061: 3
- Signal outputs: 16



Control unit UG 6911.10

- Width: 22,5 mm
- Cat. / PL acc. to EN ISO 13849-1: 4/e
- SIL CL acc. to IEC/EN 62061: 3
- Safety inputs: 8
- 2-channel safety outputs OSSD: 2



Control unit UG 6911.12/080

- Width: 22,5 mm
- Cat. / PL acc. to EN ISO 13849-1: 4/e
- SIL CL acc. to IEC/EN 62061: 3
- Safety inputs: 8
- 1-channel safety outputs OSSD: 4



Output module OSSD UG 6912.02

- Width: 22,5 mm
- Cat. / PL acc. to EN ISO 13849-1: 4/e
- SIL CL acc. to IEC/EN 62061: 3
- 2-channel safety outputs OSSD: 2



Input module UG 6913.08

- Width: 22,5 mm
- Cat. / PL acc. to EN ISO 13849-1: 4/e
- SIL CL acc. to IEC/EN 62061: 3
- Safety inputs: 8



Input module UG 6913.12

- Width: 22,5 mm
- Cat. / PL acc. to EN ISO 13849-1: 4/e
- SIL CL acc. to IEC/EN 62061: 3
- Safety inputs: 12



Output module relay UG 6914.04/000

- Width: 22,5 mm
- Cat. / PL acc. to EN ISO 13849-1: 4/e
- SIL CL acc. to IEC/EN 62061: 3
- Safety NO contacts: 4



Input / Output module UG 6916.10

- Width: 22,5 mm
- Cat. / PL acc. to EN ISO 13849-1: 4/e
- SIL CL acc. to IEC/EN 62061: 3
- Safety inputs: 8
- 2-channel safety outputs OSSD: 2



Input / Output module UG 6916.12/080

- Width: 22,5 mm
- Cat. / PL acc. to EN ISO 13849-1: 4/e
- SIL CL acc. to IEC/EN 62061: 3
- Safety inputs: 8
- 1-channel safety outputs OSSD: 4



Speed monitoring module UG 6917/002

- Width: 22,5 mm
- Cat. / PL acc. to EN ISO 13849-1: 4/e
- SIL CL acc. to IEC/EN 62061: 3
- Signal generator: 2 Proximity sensors



Bus Extender UG 6918

- Width: 22,5 mm
- Cat. / PL acc. to EN ISO 13849-1: 4/e
- SIL CL acc. to IEC/EN 62061: 3



Fieldbus module EtherCAT UG 6956

- Width: 22,5 mm



Output module OSSD UG 6912.04

- Width: 22,5 mm
- Cat. / PL acc. to EN ISO 13849-1: 4/e
- SIL CL acc. to IEC/EN 62061: 3
- 2-channel safety outputs OSSD: 4



Output module relay UG 6912.14

- Width: 22,5 mm
- Cat. / PL acc. to EN ISO 13849-1: 4/e
- SIL CL acc. to IEC/EN 62061: 3
- Safety NO contacts: 1 x 2
- NC contacts: 1 x 1



Output module relay UG 6912.28

- Width: 22,5 mm
- Cat. / PL acc. to EN ISO 13849-1: 4/e
- SIL CL acc. to IEC/EN 62061: 3
- Safety NO contacts: 2 x 2
- NC contacts: 2 x 1



Input module UG 6913.16

- Width: 22,5 mm
- Cat. / PL acc. to EN ISO 13849-1: 4/e
- SIL CL acc. to IEC/EN 62061: 3
- Safety inputs: 16



Output module relay UG 6914.04/008

- Width: 22,5 mm
- Cat. / PL acc. to EN ISO 13849-1: 4/e
- SIL CL acc. to IEC/EN 62061: 3
- Safety NO contacts: 4



Speed monitoring module UG 6917/102

- Width: 22,5 mm
- Cat. / PL acc. to EN ISO 13849-1: 4/e
- SIL CL acc. to IEC/EN 62061: 3
- Signal generator: 2 Proximity sensors, 1 TTL Encoder



Speed monitoring module UG 6917/112

- Width: 22,5 mm
- Cat. / PL acc. to EN ISO 13849-1: 4/e
- SIL CL acc. to IEC/EN 62061: 3
- Signal generator: 2 Proximity sensors, 2 TTL Encoder



Speed monitoring module UG 6917/202

- Width: 22,5 mm
- Cat. / PL acc. to EN ISO 13849-1: 4/e
- SIL CL acc. to IEC/EN 62061: 3
- Signal generator: 2 Proximity sensors, 1 HTL Encoder



Speed monitoring module UG 6917/222

- Width: 22,5 mm
- Cat. / PL acc. to EN ISO 13849-1: 4/e
- SIL CL acc. to IEC/EN 62061: 3
- Signal generator: 2 Proximity sensors, 2 HTL Encoder



Speed monitoring module UG 6917/302

- Width: 22,5 mm
- Cat. / PL acc. to EN ISO 13849-1: 4/e
- SIL CL acc. to IEC/EN 62061: 3
- Signal generator: 2 Proximity sensors, 1 Sin/Cos Encoder



Speed monitoring module UG 6917/332

- Width: 22,5 mm
- Cat. / PL acc. to EN ISO 13849-1: 4/e
- SIL CL acc. to IEC/EN 62061: 3
- Signal generator: 2 Proximity sensors, 2 Sin/Cos Encoder



Fieldbus module CANopen UG 6951

- Width: 22,5 mm



Fieldbus module PROFIBUS DP UG 6952

- Width: 22,5 mm



Fieldbus module PROFINET UG 6954

- Width: 22,5 mm



Fieldbus module Ethernet/IP UG 6955

- Width: 22,5 mm



Fieldbus module Modbus TCP/IP UG 6958

- Width: 22,5 mm



Fieldbus module Modbus RTU UG 6959

- Width: 22,5 mm

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +(727)345-47-04

Беларусь +(375)257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: ddo@nt-rt.ru || сайт: <https://dold.nt-rt.ru/>