

Измерительные реле для контроля физических величин

Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +(727)345-47-04

Беларусь +(375)257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: ddo@nt-rt.ru || сайт: <https://dold.nt-rt.ru/>



Sensorless Standstill Monitor UG 9146

- Width: 22,5 mm
- Measuring range max.: 400 mV, 4 V
- Auxiliary voltage: DC
- Classification: Sensorless, Stillstandsüberwachung
- Operate delay: Yes



Thermistor Motor Protection Relay MK 9163N ATEX

- Width: 22,5 mm
- Measuring range max.: > 3.8 kΩ
- Auxiliary voltage: AC, AC/DC
- Classification: Thermistor-Motorschutz



Thermistor Motor Protection Relay MK 9003 ATEX

- Width: 22,5 mm
- Measuring range max.: > 3.1 kΩ
- Auxiliary voltage: AC, DC
- Classification: Thermistor-Motorschutz



Temperature Monitoring Relay SL 9094

- Width: 35 mm
- Measuring range max.: 250 °C
- Auxiliary voltage: AC
- Classification: Temperaturüberwachung



Temperature Monitoring Relay SK 9094

- Width: 17,5 mm
- Measuring range max.: 250 °C
- Auxiliary voltage: AC/DC
- Classification: Temperaturüberwachung



Temperature Monitoring Relay IL 9094

- Width: 35 mm
- Measuring range max.: 250 °C
- Auxiliary voltage: AC
- Classification: Temperaturüberwachung



Temperature Monitoring Relay IK 9094

- Width: 17,5 mm
- Measuring range max.: 250 °C
- Auxiliary voltage: AC/DC
- Classification: Temperaturüberwachung



Standstill Monitor BD 5936

- Width: 45 mm
- Auxiliary voltage: AC, AC/DC
- Classification: Stillstandsüberwachung



Speed Monitor MH 9055

- Width: 45 mm
- Measuring range max.: 120000 IPM
- Auxiliary voltage: AC/DC
- Classification: Drehzahlüberwachung



Speed Monitor MK 9055N

- Width: 22,5 mm
- Measuring range max.: 120000 IPM
- Auxiliary voltage: AC, DC
- Classification: Drehzahlüberwachung



Speed Monitor IK 9055

- Width: 17,5 mm
- Measuring range max.: 600000 IPM
- Auxiliary voltage: DC
- Classification: Drehzahlüberwachung
- Operate delay: Yes



Speed Monitor IL 9055

- Width: 35 mm
- Measuring range max.: 600000 IPM
- Auxiliary voltage: AC
- Classification: Drehzahlüberwachung
- Operate delay: Yes



Thermistor Motor Protection Relay MK 9163N

- Width: 22,5 mm
- Measuring range max.: > 3.8 kΩ
- Auxiliary voltage: AC, AC/DC
- Classification: Thermistor-Motorschutz



Thermistor Motor Protection Relay BA 9038

- Width: 45 mm
- Measuring range max.: > 3 kΩ
- Auxiliary voltage: AC, AC/DC
- Classification: Thermistor-Motorschutz



Level Sensing Relay MK 9151

- Width: 22,5 mm
- Measuring range max.: 450 kΩ
- Auxiliary voltage: AC, DC
- Classification: Füllstandsüberwachung
- Operate delay: Yes



Speed Monitor BA 9055

- Width: 45 mm
- Measuring range max.: 10000 IPM
- Auxiliary voltage: AC, DC
- Classification: Drehzahlüberwachung
- Operate delay: Yes



Thermistor Motor Protection Relay BA 9039

- Width: 45 mm
- Measuring range max.: > 3 kΩ
- Auxiliary voltage: AC, DC
- Classification: Thermistor-Motorschutz



Temperature Monitoring Relay BA 9094

- Width: 45 mm
- Measuring range max.: 100 °C
- Auxiliary voltage: AC, DC, AC/DC
- Classification: Temperaturüberwachung



Valve Monitor IK 9076

- Width: 17,5 mm
- Measuring range max.: < 0,7 A
- Auxiliary voltage: Without
- Classification: Ventilüberwachung



Standstill Monitor IK 9144

- Width: 17,5 mm
- Measuring range max.: 300000 IPM
- Auxiliary voltage: DC
- Classification: Stillstandsüberwachung



Standstill Monitor IL 9144

- Width: 35 mm
- Measuring range max.: 300000 IPM
- Auxiliary voltage: AC
- Classification: Stillstandsüberwachung



Level Sensing Relay IL 9151

- Width: 35 mm
- Measuring range max.: 450 kΩ
- Auxiliary voltage: AC, DC
- Classification: Füllstandsüberwachung
- Operate delay: Yes



Thermistor Motor Protection Relay IL 9163

- Width: 35 mm
- Measuring range max.: > 3.8 kΩ
- Auxiliary voltage: AC, AC/DC
- Classification: Thermistor-Motorschutz



Speed monitor MH 9055/5__

- Width: 45 mm
- Measuring range max.: 120000 IPM
- Auxiliary voltage: AC, DC
- Classification: Drehzahlüberwachung



Thermistor motor protection relay MK 9052

- Width: 22,5 mm
- Measuring range max.: > 3 kΩ
- Auxiliary voltage: AC, DC
- Classification: Thermistor-Motorschutz



Speed monitor MK 9055N/5__

- Width: 22,5 mm
- Measuring range max.: 120000 IPM
- Auxiliary voltage: AC, DC
- Classification: Drehzahlüberwachung



Level Sensing Relay MK 9151N

- Width: 22,5 mm
- Measuring range max.: 450 kΩ
- Auxiliary voltage: AC, DC
- Classification: Füllstandsüberwachung
- Operate delay: Yes



Temperature monitor MK 9162

- Width: 22,5 mm
- Auxiliary voltage: AC
- Classification: Temperaturüberwachung



Speed Monitor SK 9055

- Width: 17,5 mm
- Measuring range max.: 600000 IPM
- Auxiliary voltage: DC
- Classification: Drehzahlüberwachung
- Operate delay: Yes



Valve Monitor SK 9076

- Width: 17,5 mm
- Measuring range max.: < 0,7 A
- Auxiliary voltage: Without
- Classification: Ventilüberwachung



Standstill Monitor SK 9144

- Width: 17,5 mm
- Measuring range max.: 300000 IPM
- Auxiliary voltage: DC
- Classification: Stillstandsüberwachung



Speed Monitor SL 9055

- Width: 35 mm
- Measuring range max.: 600000 IPM
- Auxiliary voltage: AC
- Classification: Drehzahlüberwachung
- Operate delay: Yes



Standstill Monitor SL 9144

- Width: 35 mm
- Measuring range max.: 300000 IPM
- Auxiliary voltage: AC
- Classification: Stillstandsüberwachung



Level Sensing Relay SL 9151

- Width: 35 mm
- Measuring range max.: 450 kΩ
- Auxiliary voltage: AC, DC
- Classification: Füllstandsüberwachung
- Operate delay: Yes



Thermistor Motor Protection Relay SL 9163

- Width: 35 mm
- Measuring range max.: > 3.8 kΩ
- Auxiliary voltage: AC, AC/DC
- Classification: Thermistor-Motorschutz

Noise filter LG 5130



- 1- / 3-phase: 3
- Width: 22,5 mm
- Nominal voltage UN max. without PE connection: 3 AC 1000 V
- Nominal voltage UN max. with PE connection: 3/N AC 860 / 500 V

Noise filter MK 5130N



- 1- / 3-phase: 3
- Width: 22,5 mm
- Nominal voltage UN max. without PE connection: 3 AC 1000 V
- Nominal voltage UN max. with PE connection: 3/N AC 860 / 500 V

Standard probe OA 5640



По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +(727)345-47-04

Беларусь +(375)257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: ddo@nt-rt.ru || сайт: <https://dold.nt-rt.ru/>